Model GL300

Data Logger Kit

Connect the i-button reader to U1 (Note the i-Button reader is not supported on U2). Attach the GL300 to the i-Button reader port and the MFM300 will detect the GL300's presence and display GL300 data logger menu. If the GL300 has been programmed for a mission, the mission description will be displayed. To program a mission select this menu option to re-program and launch the GL300 on a new mission (see instruction manual for full details).

Conecte el lector de i-Button a U1 (Note que el lector de i-Button no está soportado en U2). Fije el GL300 al puerto de lectura del
i-Button y el MFM300 detectará la presencia del GL300 e desplegará el menú de registro de datos del GL300. Si el GL300 ha sido
programado para una misión, aparecerá la descripción de la misión. Para programar la misión seleccione esta opción de menú para reprogramar y lanzar el GL300 en una nueva misión (ver el manual de instrucciones para detalles completos).

Connectez le lecteur i-Button à U1 (remarque : le lecteur i-Button n'est pas supporté sur U2). Fixez le GL300 au port du lecteur i-Button et le MFM300 détectera la présence du GL300 et affichera le menu du collecteur de données GL300. Si le GL300 a été programmé pour une mission, la description de la mission s'affichera. Pour programmer une mission, choisissez cette option du menu pour
re-programmer et lancer le GL300 pour une nouvelle mission (voir le manuel d'instructions pour les détails complets).